





MT2-1.2-143

6, Moskovskiy Avenue, 04073, Kiev, Ukraine,
Tel: (380-44)-490-93-02, (380-44)-464-70-51, Tel/Fax: (380-44)-419 90 30,
E-mail: Modul@modulua.kiev.ua, [http:// www.spf-modul.com](http://www.spf-modul.com)

Drawing




Performance Specification

Parameters	at $T_h = 27^{\circ}\text{C}$	at $T_h = 50^{\circ}\text{C}$
I max, Amps	7.7	7.7
V max, Volts	16.5	18.5
Q max, Watts	80	88
ΔT max (min), K	68	78
R, Ohm	2	2.2

I_{max} – Input current at $Q_c=0$, $\Delta T=\Delta T_{\text{max}}$;
Q_{max} – Maximum heat pumping capacity at $\Delta T=0$, $I=I_{\text{max}}$;
V_{max} – DC input voltage at $Q_c=0$, $I=I_{\text{max}}$;
 ΔT_{max} – Maximum temperature difference at $Q_c=0$, $I=I_{\text{max}}$;
T_h – Temperature at hot side.

Maximum operating temperature 90°C

Custom designed modules are available.



MT2-1.2-143

6, Moskovskiy Avenue, 04073, Kiev, Ukraine,
Tel: (380-44)-490-93-02, (380-44)-464-70-51, Tel/Fax: (380-44)-419 90 30,
E-mail: Modul@modulua.kiev.ua, [http:// www.spf-modul.com](http://www.spf-modul.com)

